



**CONFIGURATION**

X	Control	-
X	Adjustment Range	-
N	Seal Material	Buna-N
/AP	Material/Coating	Stainless Steel, Passivated

This cavity plug allows ports 1 and 2 to remain open and blocks port 3.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-19A
Series	4
Max. Op. Press.	350 bar
Port Configuration	3 Port
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Seal kit - Cartridge	Buna: 990019007
Seal kit - Cartridge	Polyurethane: 990019002
Seal kit - Cartridge	Viton: 990019006
Model Weight	0.65 kg.

**CONFIGURATION OPTIONS**

Model Code Example: XJOAXXN/AP

<b>CONTROL</b>	(X)	<b>ADJUSTMENT RANGE</b>	(X)	<b>SEAL MATERIAL</b>	(N)	<b>MATERIAL/COATING</b>	(/AP)
X -		X -		N Buna-N V Viton		/AP Stainless Steel, Passivated Standard Material/Coating	

**TECHNICAL FEATURES**

- Corrosion resistant cavity plugs are intended for use in corrosive environments and are identified by the model code suffix /AP (see CONFIGURATION section). The bodies of these plugs are made from high strength lean duplex stainless steel. Internal parts are made from carbon steel leaded alloy, the same as standard plugs.