



CONFIGURATION

X	Adjustment Range	-
N	Seal Material	Buna-N
(none)	Material/Coating	Standard Material/Coating

This cavity plug includes an external port open to port 1 and blocks port 2.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-8A
Series	P
Maximum Operating Pressure	350 bar
Port Configuration	2 Port
Valve Hex Size	22,2 mm
Valve Installation Torque	27 - 33 Nm
Seal kit - Cartridge	Buna: 990008007
Seal kit - Cartridge	EPDM: 990008014
Seal kit - Cartridge	Polyurethane: 990008002
Seal kit - Cartridge	Viton: 990008006
Model Weight	0.04 kg.

CONFIGURATION OPTIONS

Model Code Example: **XACAEXN**

ADJUSTMENT RANGE	(X)	SEAL MATERIAL	(N)	MATERIAL/COATING
X -		N Buna-N		Standard Material/Coating
		E EPDM		<i>IAP</i> Stainless Steel, Passivated
		V Viton		

TECHNICAL FEATURES

- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.

RELATED MODELS

- [XACA](#) All ports blocked cavity plug