


SEAL RETAINER PLATE



SEALS

Sun ISO 05 X, Y sandwich bodies are furnished with pilot drain ports, and due to the difference in the U.S. and European port locations, two different seal retainer plates are available. The ISO 05 X, Y CETOP seal retainer plate is for use with European manufactured directional valve applications only. Seal retainer plate only, seals only, and combination kits are available.

TECHNICAL DATA

Seal Material	Buna-N
Material	Zinc Plated Steel
Plate Thickness	1,27 mm
Model Weight	0.05 kg.

USED WITH

YDEL	YFEX	YFEY	BJ2	BJ3	BJ4	BJ5	BJ8	BJ9	BJA
BJB	BJC	BJK	BJO	BJP	BJW	BJX	BJY	CJ2	CJ4
CJ5	CJA	CJB	CJC	CJP	CJX	CJY	DJA	DJB	DJC
DJD	DJE	DJF	DJJ	DJK	DJL	DJM	DJN	DJO	DJP
DJR	DJS	DJT	DJU	DJW	DJX	DJY	DJZ	NJ2	NJ3
NJA	NJB	NJP	NJY	U8B	U8T	VTB	WHY	WHZ	WJF
X8K	Z3F	ZFB	ZJM	ZJN	ZJP	ZPP	ZSQ	ZSY	

TECHNICAL FEATURES

- All Sun seal plates are manufactured to current industry standards regarding passages and mounting bolt locations.
- The ISO 05 X, Y CETOP sandwich body can only be rotated about a single axis. Depending on the rotation of the body in relation to the seal retainer plate, the "A" and "B" passages can be reversed but the "P", "T", "X", and "Y" passages will remain unchanged.
- Sun ISO 05 X and Y sandwich bodies contain the drain and pilot passages for both U.S. and European valve manufacturers. The seal plate must be specified and ordered separately to ensure proper drain passage alignment with the rest of the stack.
- For use with the following European valve products: Rexroth (WEH 10), and Bosch