



CONFIGURATION

L Control	Twist/Lock (Detent) Manual Override
H Spool Configuration	Normally Open 1 to 2, Closed 1 to 3
N Seal Material	Buna-N

These pilot-stage, directional, 2-position, 3-way valves are manually operated cartridges and are available in two spool configurations; normally open 1 to 2 and normally open 1 to 3. These cartridges are designed for pilot flow applications. Manual operation is achieved via Sun's Twist/Lock manual override mechanism and is designed for intermittent (infrequent) use only.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-9A
Series	P
Capacity	1 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Valve Hex Size	22,2 mm
Valve Installation Torque	27 - 33 Nm
Seal kit - Cartridge	Buna: 990109007
Seal kit - Cartridge	EPDM: 990009014
Seal kit - Cartridge	Viton: 990109006
Model Weight	0.27 kg.

CONFIGURATION OPTIONS

Model Code Example: **DBAMLHN**

CONTROL	(L) SPOOL CONFIGURATION	(H) SEAL MATERIAL	(N)
L Twist/Lock (Detent) Manual Override	H Normally Open 1 to 2, Closed 1 to 3	N Buna-N	
D Twist/Lock (Dual) Manual Override	C Normally Open 1 to 3, Closed 1 to 2	E EPDM	
T Twist (Momentary) Manual Override		V Viton	

TECHNICAL FEATURES

- This valve is designed for intermittent use such as a manual override. The manual control assembly has a mechanical life expectancy of about 10,000 cycles.
- The manual control assembly can be easily replaced in the field without removing the cartridge from the manifold or main stage element.
- The momentary/twist control option "T" allows the operator to momentarily shift the valve by twisting the knob clockwise and releasing. Once released, the valve returns to its normal position.
- The detent/lock control option "L" allows the operator to shift the valve into a mechanically detented position by twisting the knob counter-clockwise. This detented position will be maintained until the operator twists the knob clockwise and allows the valve to return to its normal position.
- The dual-operation control option "D" allows the operator to either shift the valve momentarily by twisting the knob clockwise or shift it into a mechanically detented position by twisting counter-clockwise.
- The control on this valve is meant to be operated by a person's hand. The control should not be modified, for instance fastening a lever to the knob. Under no circumstances should the control be operated by other mechanical devices.
- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- Hardened spool and sleeve provide consistent operation, low spool leakage rates and superior wear characteristics.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

