


Relief, P to T, Port 3 External



TECHNICAL DATA

| | |
|---------------|-------------------------|
| Body Type | Sandwich |
| Interface | ISO 03 |
| Body Features | P to T, port 3 external |
| Stack Height | 44,5 mm |
| Open Cavities | 1 |
| Cavity | T-11A |
| Port Size | SAE 6 |
| Model Weight | 0.90 kg. |

CONFIGURATION

/T Modifier 65-45-12 Ductile Iron, Metric, Buna-N, Chem. Black

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

| Modifiers | Ports |
|-------------------------------|-----------------------|
| EBC, /10, /11, /15, /16, /V | Vent Port: SAE 6; |
| EBC/1A, /1B, /1F, /1G, /M, /Z | Vent Port: 1/4" BSPP; |

INCLUDED COMPONENTS

| Part | Description | Quantity |
|-------------|-------------|----------|
| 500-001-012 | O-Ring | 4 |
| 700-002 | Seal Plate | 1 |
| 811-001-006 | Pin | 1 |

CONFIGURATION OPTIONS
Model Code Example: EBC/T

MODIFIER

(/T)

- /T** 65-45-12 Ductile Iron, Metric, Buna-N, Chem. Black
- 6061-T651 Aluminum, Buna-N
- /11** 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
- /10** 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
- /V** 6061-T651 Aluminum, Viton
- /16** 6061-T651 Aluminum, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
- /15** 6061-T651 Aluminum, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II
- /M** 6061-T651 Aluminum, Metric, Buna-N
- /1B** 6061-T651 Aluminum, Metric, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
- /1A** 6061-T651 Aluminum, Metric, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
- /Z** 6061-T651 Aluminum, Metric, Viton
- /1G** 6061-T651 Aluminum, Metric, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
- /1F** 6061-T651 Aluminum, Metric, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II
- /S** 65-45-12 Ductile Iron, Buna-N, Chem. Black
- /S3** 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
- /Y** 65-45-12 Ductile Iron, Viton, Chem. Black
- /Y3** 65-45-12 Ductile Iron, Viton, Trivalent Clear Zinc with Top Sealer
- /T3** 65-45-12 Ductile Iron, Metric, Buna-N, Trivalent Clear Zinc with Top Sealer
- /W** 65-45-12 Ductile Iron, Metric, Viton, Chem. Black
- /W3** 65-45-12 Ductile Iron, Metric, Viton, Trivalent Clear Zinc with Top Sealer