



**CONFIGURATION**

<b>X</b>	Control	-
<b>X</b>	Adjustment Range	-
<b>N</b>	Seal Material	Buna-N
<b>(none)</b>	Material/Coating	Standard Material/Coating

These cavity plugs can be used for both two-port and four-port cavities and allow all ports to remain connected.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-10A, T-13A & T-31A
Series	1
Maximum Operating Pressure	350 bar
Port Configuration	2 Port / 4 Port
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006
Model Weight	0.07 kg.

**CONFIGURATION OPTIONS**

Model Code Example: **XFOAXXN**

CONTROL	(X) ADJUSTMENT RANGE	(X) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X -</b>	<b>X -</b>	<b>N</b> Buna-N E EPDM V Viton	<b>Standard Material/Coating</b> <b>/AP</b> Stainless Steel, Passivated <b>/LH</b> Mild Steel, Zinc-Nickel

**TECHNICAL FEATURES**

- Corrosion resistant cavity plugs are intended for use in corrosive environments and are identified by the model code suffix /AP (see CONFIGURATION section). The bodies of these plugs are made from high strength lean duplex stainless steel. Internal parts are made from carbon steel leaded alloy, the same as standard plugs.