



**TECHNICAL DATA**

|                        |               |
|------------------------|---------------|
| Body Type              | Line mount    |
| Interface              | None          |
| Body Features          | Ninety degree |
| Mounting Hole Diameter | 8.6 mm        |
| Mounting Hole Depth    | Through       |
| Mounting Hole Quantity | 1             |
| Open Cavities          | 1             |
| Cavity                 | T-13A         |
| Port Size              | 3/8" BSPP     |
| Model Weight           | 0.38 kg.      |

**CONFIGURATION**

**/S** Modifier 65-45-12 Ductile Iron, Buna-N, Blackened

**NOTES**

**Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

**PORT DESIGNATORS**

| Modifiers | Ports                 |
|-----------|-----------------------|
| GAU, /S   | All Ports: 3/8" BSPP; |

**CONFIGURATION OPTIONS**

**Model Code Example: GAU/S**

**MODIFIER** (S)

**/S** 65-45-12 Ductile Iron, Buna-N, Blackened  
6061-T651 Aluminum, Buna-N