


**CONFIGURATION**

<b>L</b> Control	Standard Screw Adjustment
<b>A</b> Adjustment Range	25 - 3000 psi (1,7 - 210 bar), 1000 psi (70 bar) Standard Setting
<b>N</b> Seal Material	Buna-N
<b>/AP</b> Material/Coating	Stainless Steel, Passivated

Direct-acting, pilot relief cartridges are used to remotely control the pressure setting of other pilot-operated valves. Because capacity is limited to pilot flow, these valves should be used with other higher flow valves.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-10A
Series	1
Capacity	1 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	EPDM: 990010014
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006
Model Weight	0.14 kg.

**NOTES** For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.

**CONFIGURATION OPTIONS**
**Model Code Example: RBACLAN/AP**

<b>CONTROL</b>	<b>(L) ADJUSTMENT RANGE</b>	<b>(A) SEAL MATERIAL</b>	<b>(N) MATERIAL/COATING</b>	<b>(/AP)</b>
<b>L</b> Standard Screw Adjustment	<b>A</b> 25 - 3000 psi (1,7 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	<b>/AP</b> Stainless Steel, Passivated	
<b>C</b> Tamper Resistant - Factory Set	<b>W</b> 25 - 4500 psi (1,7 - 315 bar), 1000 psi (70 bar) Standard Setting	<b>E</b> EPDM	Standard Material/Coating	
<b>J</b> Capped Screw Adjustment	<b>B</b> 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar) Standard Setting	<b>V</b> Viton	<b>/LH</b> Mild Steel, Zinc-Nickel	
<b>K</b> Handknob	<b>C</b> 25 - 6000 psi (1,7 - 420 bar), 1000 psi (70 bar) Standard Setting			
<b>O</b> Handknob with Panel Mount	<b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting			
	<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting			

## TECHNICAL FEATURES

- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- Main stage orifice is protected by a 150-micron stainless steel screen.
- Suitable for use in load holding applications.
- Back pressure on the tank port (port 2) is directly additive to the valve setting at a 1:1 ratio.
- W and Y controls (where applicable) can be specified with or without a special setting. When no special setting is specified, the valve is adjustable throughout its full range using the W or Y control. When a special setting is specified, this setting represents the maximum setting of the valve.
- Corrosion resistant cartridge valves are intended for use in corrosive environments and are identified by the model code suffix /AP for external stainless steel components, or /LH for external zinc-nickel plated components. See the CONFIGURATION section for all options. For further details, please see the Materials of Construction page located under TECH RESOURCES.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

## PERFORMANCE CURVES

