



CONFIGURATION

| | | |
|---------------|------------------|---------------------------|
| X | Control | - |
| X | Adjustment Range | - |
| N | Seal Material | Buna-N |
| (none) | Material/Coating | Standard Material/Coating |

This cavity plug allows all ports to remain open.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------------|-------------------------|
| Cavity | T-8A |
| Series | P |
| Maximum Operating Pressure | 350 bar |
| Port Configuration | 2 Port |
| Valve Hex Size | 22,2 mm |
| Valve Installation Torque | 27 - 33 Nm |
| Seal kit - Cartridge | Buna: 990008007 |
| Seal kit - Cartridge | Polyurethane: 990008002 |
| Seal kit - Cartridge | Viton: 990008006 |
| Model Weight | 0.05 kg. |

CONFIGURATION OPTIONS

Model Code Example: **XAOAXXN**

| CONTROL | (X) ADJUSTMENT RANGE | (X) SEAL MATERIAL | (N) MATERIAL/COATING |
|------------|----------------------|--|--|
| X - | X - | N Buna-N E EPDM V Viton | N Standard Material/Coating IAP Stainless Steel, Passivated |