


**CONFIGURATION**

<b>X</b> Control	-
<b>X</b> Adjustment Range	-
<b>N</b> Seal Material	Buna-N
<b>/AP</b> Material/Coating	Stainless Steel, Passivated

This cavity plug allows all ports to remain open.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-8A
Series	P
Maximum Operating Pressure	350 bar
Port Configuration	2 Port
Valve Hex Size	22,2 mm
Valve Installation Torque	27 - 33 Nm
Seal kit - Cartridge	Buna: 990008007
Seal kit - Cartridge	Polyurethane: 990008002
Seal kit - Cartridge	Viton: 990008006
Model Weight	0.09 kg.

**CONFIGURATION OPTIONS**
**Model Code Example: XAOAXXN/AP**

<b>CONTROL</b>	<b>(X) ADJUSTMENT RANGE</b>	<b>(X) SEAL MATERIAL</b>	<b>(N) MATERIAL/COATING</b>	<b>(/AP)</b>
<b>X -</b>	<b>X -</b>	<b>N</b> Buna-N E EPDM V Viton	<b>/AP</b> Stainless Steel, Passivated Standard Material/Coating /LH Mild Steel, Zinc-Nickel	