



CONFIGURATION

X	Control	-
X	Adjustment Range	-
V	Seal Material	Viton
(none)	Material/Coating	Standard Material/Coating

This cavity plug allows ports 1 and 2 to remain open and blocks port 3.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-2A
Series	2
Maximum Operating Pressure	350 bar
Port Configuration	3 Port
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Seal kit - Cartridge	Buna: 990202007
Seal kit - Cartridge	Polyurethane: 990002002
Seal kit - Cartridge	Viton: 990202006
Model Weight	0.16 kg.

CONFIGURATION OPTIONS

Model Code Example: **XBOAXXV**

CONTROL	(X) ADJUSTMENT RANGE	(X) SEAL MATERIAL	(V) MATERIAL/COATING
X -	X -	V Viton N Buna-N	Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel

TECHNICAL FEATURES

- Corrosion resistant cavity plugs are intended for use in corrosive environments and are identified by the model code suffix /AP (see CONFIGURATION section). The bodies of these plugs are made from high strength lean duplex stainless steel. Internal parts are made from carbon steel leaded alloy, the same as standard plugs.

RELATED MODELS

- [XBOAE](#) Port 1 to 2 open, port 3 blocked cavity plug with SAE-4 external port