



**CONFIGURATION**

X	Control	-
X	Adjustment Range	-
V	Seal Material	Viton
/AP	Material/Coating	Stainless Steel, Passivated

This cavity plug blocks all ports.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-11A
Series	1
Port Configuration	3 Port
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal kit - Cartridge	Buna: 990011007
Seal kit - Cartridge	Polyurethane: 990011002
Seal kit - Cartridge	Viton: 990011006
Model Weight	0.11 kg.

**CONFIGURATION OPTIONS**

Model Code Example: XECAXXV/AP

CONTROL	(X)	ADJUSTMENT RANGE	(X)	SEAL MATERIAL	(V)	MATERIAL/COATING	(/AP)
X -		X -		V Viton		/AP Stainless Steel, Passivated	
				E EPDM		Standard Material/Coating	
				N Buna-N		/LH Mild Steel, Zinc-Nickel	

**TECHNICAL FEATURES**

- Corrosion resistant cavity plugs are intended for use in corrosive environments and are identified by the model code suffix /AP (see CONFIGURATION section). The bodies of these plugs are made from high strength lean duplex stainless steel. Internal parts are made from carbon steel leaded alloy, the same as standard plugs.

**RELATED MODELS**

- [XECAB](#) Cavity plug
- [XECAE](#) Port 1 to external port, ports 2 and 3 blocked cavity plug