



Sun offers replacement seal kits for all cartridge models. These kits include all of the external seals on the cartridge along with installation instructions. Seal kits are available in Buna-N and Viton for all models, along with EPDM and polyurethane for many models. Please note: Converting the external seals from one material to another does not ensure fluid compatibility with that material due to the existence of internal seals within the cartridge.

CARTRIDGE INSTALLATION DATA

Series	0
Cartridge Thread	M16
Valve Hex Size	19,1 mm
Valve Installation Torque	27 - 33 Nm
Cavity	T-162A
Model Weight	0.00 kg.

NOTES

- Install back-up rings and O-rings as shown in views.
- When installing continuous back-up rings, use the same technique and the same care used to install O-rings.
- When installing cartridge - be sure to torque to recommended value.

USED WITH

CDAP	CDAQ	CNAC	CNBC	CSAN	CSAW	CSAY	CXAD	CXBA	CXBG
CXBM	DFBD	DFBE	DFBF	DFBG	DTBF	FCBB	FPBD	FPBE	FPBF
FPBG	FPBI	FPBJ	FPBM	FPBN	FPBU	FQBA	FXBA	NCBB	NFBC
RDBA	RPCC	RQCB	XZCA	XZCC	XZOA	XZOC			

TECHNICAL FEATURES

- The shelf life for this cartridge seal kit is ten years from date of purchase. This date will be printed on the kit packaging.