



**CONFIGURATION**

<b>X</b>	Control	Standard Pilot
<b>C</b>	Spool Configuration	Blocked Center
<b>N</b>	Seal Material	Buna-N
<b>(none)</b>	Material/Coating	Standard Material/Coating

Three-position, 4-way directional cartridges are spring-centered, 6-port directional valves that can be configured from a choice of spool options. The supply port is port 3 and all ports will accept 5000 psi (350 bar). Capacity for these pilot-to-shift valves is dependent on the spool type specified.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-61A
Series	1
Capacity	28 - 40 L/min.
Minimum Pilot Pressure Required to Shift Valve	12 bar
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Volume Displacement	0,33 cc
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal kit - Cartridge	Buna: 990061007
Seal kit - Cartridge	Polyurethane: 990061002
Seal kit - Cartridge	Viton: 990061006
Model Weight	0.21 kg.

**CONFIGURATION OPTIONS**

Model Code Example: **DCCCXCN**

<b>CONTROL</b>	<b>(X) SPOOL CONFIGURATION</b>	<b>(C) SEAL MATERIAL</b>	<b>(N) MATERIAL/COATING</b>
<b>X</b> Standard Pilot	<b>C</b> Blocked Center	<b>N</b> Buna-N	Standard Material/Coating
	A A to T Center	V Viton	/AP Stainless Steel, Passivated
	B B to T Center		/LH Mild Steel, Zinc-Nickel
	F Closed Center, A and B to T		
	H Open Center		
	N P to A and B to T Center		
	R Regen Center		
	T Tandem Center		
	W A and B Bleed to T Center		
	Y A and B to T Center		

**TECHNICAL FEATURES**

- All ports will accept 5000 psi (350 bar), including the x and y pilot ports (port 5 and port 6).
- The reason for the different capacities, or performance limits, for the different spool configurations are flow forces. Flow forces are proportional to flow and pressure drop. Typically, they resist the opening of a passage. Spool configurations that open passages as they spring center are the most susceptible. If the flow forces due to the flow and pressure conditions exceed the centering spring force the valve may not shift completely. Higher flows may be used at lower pressures.
- Leakage listed in technical data is for each path.
- The pilot ports, 5 and 6, are positively sealed from the work ports.
- Hardened spool and sleeve provide consistent and low spool leakage rates and excellent wear characteristics.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

**PERFORMANCE CURVES**

