



CONFIGURATION

B	Control	External 1/4 BSPP Port
X	Adjustment Range	-
V	Seal Material	Viton
(none)	Material/Coating	Standard Material/Coating

The single ball shuttle connects the higher of two work ports to the signal or common port. The signal is sensed at an external port located in the hex-end of the cartridge.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-13A
Series	1
Capacity	10 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006
Model Weight	0.10 kg.

CONFIGURATION OPTIONS

Model Code Example: **CSAABXV**

CONTROL	(B) ADJUSTMENT RANGE	(X) SEAL MATERIAL	(V) MATERIAL/COATING
B External 1/4 BSPP Port E External 4-SAE Port	X -	V Viton N Buna-N	Standard Material/Coating IAP Stainless Steel, Passivated LH Mild Steel, Zinc-Nickel

TECHNICAL FEATURES

- Shuttle cartridges feature hardened steel balls and seats for excellent wear characteristics and contamination tolerance.
- The single ball allows for the decay of the pressure signal when both load ports drop to a lower pressure.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

