



These cavity plugs can be used for both four-port and six-port cavities. When used in four-port cavities (T-21A, T-22A, T-23A and T-24A), ports 1 and 2 remain connected and ports 3 and 4 are blocked. When used in six-port cavities (T-61A, T-62A, T-63A and T-64A), ports 1, 2, 3 and 4 remain connected and ports 5 and 6 are blocked.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-24A & T-64A
Series	4
Max. Op. Press.	350 bar
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Seal kit - Cartridge	Buna: 990024007
Seal kit - Cartridge	Polyurethane: 990024002
Seal kit - Cartridge	Viton: 990024006
Model Weight	0.91 kg.

CONFIGURATION

X	Control	-
X	Adjustment Range	-
N	Seal Material	Buna-N
(none)	Material/Coating	Standard Material/Coating

CONFIGURATION OPTIONS

Model Code Example: **XQOAXXN**

CONTROL	(X) ADJUSTMENT RANGE	(X) SEAL MATERIAL	(N) MATERIAL/COATING
X -	X -	N Buna-N V Viton	Standard Material/Coating /LH Mild Steel, Zinc-Nickel