



CONFIGURATION

| | | |
|---------------|------------------|---------------------------|
| X | Control | - |
| X | Adjustment Range | - |
| N | Seal Material | Buna-N |
| (none) | Material/Coating | Standard Material/Coating |

This cavity plug blocks all ports.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---------------------------|-------------------------|
| Cavity | T-33A |
| Series | 3 |
| Max. Op. Press. | 350 bar |
| Valve Hex Size | 31,8 mm |
| Valve Installation Torque | 203 - 217 Nm |
| Seal kit - Cartridge | Buna: 990033007 |
| Seal kit - Cartridge | Polyurethane: 990033002 |
| Seal kit - Cartridge | Viton: 990033006 |
| Model Weight | 0.47 kg. |

CONFIGURATION OPTIONS

Model Code Example: **XTCAXXN**

| CONTROL | (X) ADJUSTMENT RANGE | (X) SEAL MATERIAL | (N) MATERIAL/COATING |
|----------------|-----------------------------|-----------------------------------|----------------------------------------------------------------------------|
| X - | X - | N Buna-N V Viton | Standard Material/Coating /AP Stainless Steel, Passivated |