



TECHNICAL DATA

Body Type	Line mount
Interface	Banjo Bolt
Body Features	Through port 2 with gauge port
Banjo Bolt Installation Torque	53 lb. ft. to 58 lb. ft. (70 Nm to 77 Nm)
Banjo Bolt Hex	.94
Open Cavities	1
Cavity	T-21A
Port Size	3/8" BSPP
Model Weight	1.29 kg.

CONFIGURATION

/S Modifier 65-45-12 Ductile Iron, Buna-N, Chem. Black

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

Modifiers	Ports
X5Y, /10, /11	Ports 1 & 2: 3/8" BSPP; Ports 3 & 4: 1/4" BSPP;

INCLUDED COMPONENTS

Part	Description	Quantity
280-048-001	Orifice	1
330-018-002	Plug	2
330-073-002	Connector	1
505-012-002	O-Ring	1

CONFIGURATION OPTIONS
Model Code Example: X5Y/S

MODIFIER

(/S)

- /S** 65-45-12 Ductile Iron, Buna-N, Chem. Black
- 6061-T651 Aluminum, Buna-N
- /11** 6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
- /10** 6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
- /S3** 65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer