



**CONFIGURATION**

<b>X</b>	Control	-
<b>X</b>	Adjustment Range	-
<b>N</b>	Seal Material	Buna-N
<b>(none)</b>	Material/Coating	Standard Material/Coating

This cavity plug allows all ports to remain open.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-162A
Series	0
Maximum Operating Pressure	350 bar
Port Configuration	2 Port
Valve Hex Size	19,1 mm
Valve Installation Torque	27 - 33 Nm
Seal kit - Cartridge	Buna: 990162007
Seal kit - Cartridge	EPDM: 990162014
Seal kit - Cartridge	Polyurethane: 990162002
Seal kit - Cartridge	Viton: 990162006
Model Weight	0.06 kg.

**CONFIGURATION OPTIONS**

Model Code Example: **XZOAXXN**

CONTROL	(X)	ADJUSTMENT RANGE	(X)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> -		<b>X</b> -		<b>N</b> Buna-N		Standard Material/Coating
				<b>E</b> EPDM		/AP Stainless Steel, Passivated
				<b>V</b> Viton		/LH Mild Steel, Zinc-Nickel

**TECHNICAL FEATURES**

- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.