


Relief, A to B and B to A



TECHNICAL DATA

Body Type	Sandwich
Interface	ISO 07
Body Features	A to B and B to A
Stack Height	50 mm
Open Cavities	2
Cavity	T-10A
Model Weight	2.84 kg.

CONFIGURATION

/S Modifier 65-45-12 Ductile Iron, Buna-N, Blackened

NOTES

Important: Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

INCLUDED COMPONENTS

Part	Description	Quantity
340-004	Pipe Plug	2
500-001-111	O-Ring	2
500-001-118	O-Ring	4
700-006	Seal Plate	1
811-001-006	Pin	2

CONFIGURATION OPTIONS

Model Code Example: CKY/S

MODIFIER (S)

- /S** 65-45-12 Ductile Iron, Buna-N, Blackened
- 6061-T651 Aluminum, Buna-N
- /V 6061-T651 Aluminum, Viton
- /Y 65-45-12 Ductile Iron, Viton, Blackened

MANIFOLD FACES

FACE GRID

1	2	3	4
5	6	7	8
9	10	11	12

Face 2



Face 5



Face 6

□

Face 7

□

Face 8

□

Face 10

□